

SPECIFICATIONS

OVERVIEW

	Model	9150-R+
Main	OS	Linux 3.4.39 QT based
	Processor	Cortex A9 1.4GHz
	Size	15"
Display	Screen	TFT
	Resolution	1920*1080
	Color	16,000k colors
	Brightness (cd/m ²)	250.0
	Backlight	LED
	Backlight Lifetime	50,000 hours
	Touch Panel	High precision four-wire resistive
Storage	Memory	512 MB
	Flash	4 GB
	SD Card Slot	Yes
	USB Port	USB2.0 Host + USB2.0 Client
RTC	Real-time clock	Yes
	Calendar	Yes
	COM1	CN1:RS422/RS485 CN2: RS232
	COM2	CN1:RS485 CN2: RS232
I/O Port	COM3	RS485
	Ethernet	x1
	CANopen	--
Power	Wi-Fi	--
	4G LTE	--
	Rated Power	< 20W
	Power Voltage	DC 24V
	Input range	DC 12 ~ 28V
Enclosure	Shell Color	Silvery
	Shell Material	Aluminium+Steel Plate
	Overall Size (mm)	402.9W*253.2H*47.0D
	Mounting Size (mm)	394.0W*244.0H
	Mounting Method	Panel Mount, VESA 75*75mm
	Weight (Kg)	3.1
Environment	Working Temperature	-10 ~ 60°C
	Storage Temperature	-20 ~ 70°C
	Humidity	10 ~ 90%RH (Non-condensing)
	Vibration Resistance	29 ~ 25 Hz (X, Y, Z direction 2G/30 minutes)
Software	Cooling	Air Cooling
	Programming	HMIEditorP
	Remote Access	LAN/WAN
	Email Alarm	--
	IP Camera	--
	Audio Output	--
Certificates	Video Player	--
	IP Code	IP65 (Front panel)
	CE	CE Marked
	FCC	FCC Class A
UL	--	



DIMENSION

